



规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating  
1.5A/contact terminal
2. 额定电压: Voltage Rating  
30V DC
3. 接触阻抗: Contact Resistance  
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC For one minute
5. 绝缘阻抗: Insulation Resistance:  
1000MEGA ohms MIN

原材料: Raw material:

1. 塑胶: Plastic cement:  
High Temperature Thermoplastics,  
LCP/PBT White/ Black
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Electroplate:

1. 端子: Contact: Plated Gold in Mating Area;  
Tin On Solder Talls
2. 外壳: Shell:  
Nickel Plating

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ± 5°

P PROJECTION

照片框

ORDER INFORMATION

USB-SRZ172BK100FX-4A-LF  
SERIES | | | | LEADFREE  
FEMALE | | | | 4 PIN A TYPE  
DIP 90° | | | | NON FLANGE  
CLIP | | | | LONG 10.0mm  
BLACK | | | | FOOTPRINT 7.25mm

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: