



RECOMMENDED P. C. B. PATTERN LAYOUT

NOTE

MATERIAL:  
 CONTACTS :PHOSPHOR BRONZE  
 INSULATOR: PBT+30% G.F. UL-0  
 SHELL : BRASS  
 BACKSHELL:SPCC  
 MATING: 35N MAX.  
 WITHDRAWAL FORCE:10N MIN.  
 DURABILITY:1500 CYCLES MIN.  
 CURRENT-MAX[AMPS] 1.5A  
 VOLTAGE-MAX[VOLTS] 30V  
 WITHSTANDING VOLTAGE 500V AC  
 CONTACT RESISTANCE 30MΩ MAX.  
 INSULATION RESISTANCE 1000MΩ MIN.  
 COLD PLATING 1u",3u",5u".... ON CONTACT AREA  
 100u" TIN PLAING ON SOLDER TAIL  
 50u" TICKEL UNDREPLATED OVER ALL  
 SHELL: NICKEL OVER ALL PLATING  
 TEMPERATURE RANGE -55°C~+85°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY	
CHECKED BY GENIUS	
UNIT / mm	SCALE 1 : 1
DATE	
SIZE A4	PJECTION

X. ±  
 .X ± 0.25  
 .XX ± 0.15  
 .XXX ± 0.05  
 ANG ±

照片框

ORDER INFORMATION

USB-SRcc-4B-LF  
 SERIES | | | LEADFREE  
 | | | 4 PIN B TYPE  
 FEMALE | | BK:BLACK  
 | | | WH:WHITE  
 | | | DIP 90°

DESCRIPTION: