



特性: Specifications:

电器: Electrical:

接触阻抗: Contact Resistance
30 milliohms MAX

耐电压: Dielectric Withstanding Voltage:
500V AC AT Sea Level

绝缘阻抗: Insulation Resistance:
100 MEGA ohms MIN

材料: Material:

塑胶: Housing: PBT

端子: Contact: Copper Alloy C2680H, T=0.2H

外壳: Shell: Spcc T=0.3H

电镀: Finish:

端子: Contact: Plated Gold in Mating Area;
Tin/ Sn Solder Tails T=0.2H

接触点镀金. 脚镀锡

外壳: Shell: Nickel 镀镍

USB-SRxxIM-4A-LF

BK:BLACK LEADFREE

WH:WHITE

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

焯倫股份有限公司

PART NO. USB-SRxxIM-4A

DWG NO. USB-SRxxIM-4A

FILE NO.

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

X. ± 0.3

.X ± 0.25

.XX ± 0.2

.XXX ±

ANG

DESCRIPTION:	USB AF DIP 90° 有蓋彎腳		
AREA	REVISIONS	DATE	