



Specifications:

Current Rating:1.5A AC/DC
 Voltage Rating:30V AC/DC
 Contact Resistance:30m ohm. Max.
 Insulation Resistance:1,000M ohm. min.
 Withstanding Voltage:500V AC For One Minute
 Operating Temperature Range:-40°C ~ +105°C
 Mechanical Performance:
 Insertion Force:3.57Kgf Max.
 Withdrawal Force:1.02Kgf Min.
 Terminal Retention Force:1.2Kgf Min.
 Material and Finish
 Insulator:PBT/LCP(UL94V-0),White
 Contact:Copper Alloy
 Plating:Gold Plated on Contact Area,
 Tin Plated on Solder Tail.
 Shell:Copper Alloy
 Plating:Nickel Plated

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ± 0.20
 .XX ± 0.15
 .XXX ± 0.10
 ANG ±

PJECTION

照片框

ORDER INFORMATION

USB-SScc-4A-LF
 SERIES | LEADFREE
 | 4 PIN A TYPE
 FEMALE | BK:BLACK
 | WH:WHITE
 SOLDER

DESCRIPTION: USB A FEMALE SOLDER TYPE