



RECOMMEND PCB LAYOUT

NOTES:

1. ELECTRICAL:

- 1) VOLTAGE CURRENT RATING: 2.0AMP,30V AC;
- 2) INSULATION RESISTANCE: 1000MΩ MIN;
- 3) CONTACT RESISTANCE: 30mΩ MAX;
- 4) WITHSTANDING VOLTAGE: 500V AC;
- 5) OPERATING TEMPERATURE:-55°C TO +85°C.

2. Mechanical:

- 1) Mating Force: 35N MAX
- 2) Unmating Force: 10N MIN.
3. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING
3	HOUSING	LCP	1	UL94V-0
2	SHELL	COPPER ALLOY	1	PLATED TIN/NICKEL
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.35

.X ± 0.30

.XX ± 0.25

.XXX ± 0.15

ANG ±

PJECTION

照片框

ORDER INFORMATION

USB-SU4cc104LCP-4A-LF  
SERIES | LCP | LEADFREE  
FEMALE | UPRIGHT | BK:BLACK | WH:WHITE  
4X01 | LONG 10.4mm | 4 PIN A TYPE

DESCRIPTION: USB AF 侧插短体10.5 平口