




MECHANICAL

INSULATOR MATERIAL:

PBT & Glass-fibre reinforced
UL 94V-0

CONTACT:

Phosphor bronze

SHELL:

Aluminum, anodize

WIRE SIZE:

AWG 24 or 26

ELECTRICAL

CURRENT RATING:

7 Amp

WITHSTANDING VOLTAGE:

AC 1200V Min. (for one minute)

INSULATION RESISTANCE:

1000M Ω Min.(at 500V DC)

CONTACT RESISTANCE:

10m Ω Max. mated

WORKING TEMPERATURE:

-55° C to +105° C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. $\pm$

.X $\pm$

.XX $\pm$

.XXX $\pm$

ANG $\pm$

PPOJECTION

照片框

ORDER INFORMATION

V35-PHB-34-LF
SERIES T T T LEADFREE
34WAY
B TYPE
HOUSING
MALE

DESCRIPTION: V.35 CONNECTOR MALE WITH METAL SHELL