



ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING: 0.5 AMPERE
 DIELECTRIC WITHSTANDING VOLTAGE: 250 VAC
 INSULATION RESISTANCE: 500 MEGOHMS MIN.
 CONTACT RESISTANCE: 80 MILLIOHMS MAX.

MATERIALS

CONTACTS: COPPER ALLOY
 INSULATOR: THERMOPLASTIC 94V-0
 SHELL: COLD ROLLER STEEL
 POSITIONS #25 AND #26 ARE RECESSED WITH RESPECT TO THE OTHER 48 POSITIONS FOR LMFB.

FINISHES

CONTACT: 30 μ" MIN. GOLD ON MATING END;
 TIN ON TERMINATION END;
 ALL UNDERPLATED NICKEL
 SHELL: NICKEL OVER COPPER

ENVIRONMENT

OPERATION TEMPERATURE: -55°C TO + 85°C

PC BOARD EDGE
 Recommended P C Board Layout

RoHS Compliant

TOLERANCES ARE

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

VHC-SRWN-050-LF
 SERIES | | | LEADFREE
 | | | 50 WAY
 | | | NUT
 | | | 90° SMT
 FEMALE | | | DIP 90°

DESCRIPTION: VHDCI 0.8mm R/A Receptacle

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com