

Features:

- 2 ~ 15 circuits available
- Material: UL 94V-0 nylon 66
- Color: White

Specification:


- Current rating: 3A AC, DC (#20, #22 AWG)
- Voltage rating: 250V AC, DC
- Contact resistance: Initial value/10mΩ Max.
- After environmental testing/20mΩ Max.
- Insulation resistance: 1000MΩ Min.
- Withstanding voltage: 1000V AC/minute
- Temperature range: -25°C ~ 85°C
(including temperature rise in
applying electrical current)

Dimensional Information (mm)


Circuits	Dim. A	Dim. B
N	2.5 x (N - 1)	A + 4.8

&& N = 2 ~ 15


2P






3P



4P



5P ~ 15P



照片框

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.40
.XX ± 0.25
.XXX ± 0.08
ANG ±

ORDER INFORMATION

XA-H-xx-LF
SERIES | LEADFREE
02~15 WAY
HOUSING

DESCRIPTION: .098"(2.5mm) Crimp Terminal Housing