



### WIRING DIAGRAM

|        | P1 |   | P2  |
|--------|----|---|-----|
| RED    | 1  | — | S/T |
| BLUE   | 2  | — | S/T |
| GREEN  | 3  | — | S/T |
| YELLOW | 4  | — | S/T |
| WHITE  | 5  | — | S/T |
| BLACK  | 6  | — | S/T |
| BROWN  | 7  | — | S/T |
| PURPLE | 8  | — | S/T |

|     |           |        |            |                                                  |
|-----|-----------|--------|------------|--------------------------------------------------|
|     |           |        |            |                                                  |
|     |           |        |            |                                                  |
|     |           |        |            |                                                  |
| 3   | TUBE      | 8      | PCS        | SHRINK TUBE ø2.5*10mm #BK                        |
| 2   | CONNECTOR | 1      | SET        | MIC 8P MALE ø16mm                                |
| 1   | CABLE     | 7<br>1 | PCS<br>PCS | UL1007 24AWG 130*4*7mm<br>UL1007 24AWG 425*4*7mm |
| NO. | PART NO.  | Q'TY   | UNITS      | DESCRIPTION                                      |

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PPOJECTION

照片框

### ORDER INFORMATION

XLRX1-080024-M42C5-LF

SERIES

08 WAY

24AWG

MALE

425mm

LEADFREE

DESCRIPTION: MIC 8P MALE /TIN