







PCB Layout
(Top View)



Material and Finish

1. Housing: Nylon 6T (UL94V-0), Black.
2. Terminal: Copper Alloy (t=0.40mm), Gold Plating.

Electrical Characteristics

1. Current Rating: 1.0 Amp. Maximum.
2. Dielectric Withstand Voltage:
600V AC RMS for 60Seconds.
3. Insulation Resistance: 1,000M Ohms Min. at 500V DC.
4. Contact Resistance: 30m Ohms Maximum.

Mechanical Characteristics

1. Operating Temperature: -55°C ~ +105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

Y-D46-2Xxx-LF
SERIES LEADFREE
2X02:04WAY
2X50:100WAY
HIGH 4.6mm
DIP 180°

DESCRIPTION: 1.27*2.54mm Post Header Receptacle PCB Mount Vertical Type Dual Rows