



PCB LAYOUT

## SPECIFICATIONS

- \* Current Rating : 1 Amps
- \* Insulator resistance: 5000 Megohms min.
- \* Dielectric withstanding: AC 500 V
- \* Operating Temperature: -40°-+105°C
- \* Max Processing Temp: 230° for 30~60 seconds  
(260° for 10 seconds)
- \* Contact Material: Phosphor bronze
- \* Housing: L.C.P (UL 94 V-0)

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.20

.X ± 0.15

.XX ± 0.10

.XXX ± 0.05

ANG ±

PPOJECTION

照片框

**ORDER INFORMATION**

YA-V36XC-1XxxL-LF

SERIES	180°SMT	HIGH 3.6mm	CAP	NON POST	LEADFREE	L TYPE FOOT POSITION
					1X02:02WAY	1X50:50WAY

DESCRIPTION: 1.27mm SMD Socket (Straight/Base:3.6mm)