



Recommended P.C.B Layout

**MATERIAL**



Contact Pin : Phosphor Bronze  
 Insulator: NY6T UL94V-0

**SPECIFICATION**

Current Rate : 1 AMP  
 Insulation Resistance : 5000MΩMin.  
 Contact Resistance : 20mΩMax.  
 Dielectric Voltage : AC 500V for one minute  
 Operating Temperature: -40°C to +105°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X. ±  
 .X ± 0.30  
 .XX ± 0.20  
 .XXX ±  
 ANG ± 3°

照片框

**ORDER INFORMATION**

YA-V45XC-2X08-LF  
 SERIES | | | | LEADFREE  
 | | | | 16 WAY  
 | | | | CAP  
 | | | | NON POST  
 | | | | HIGH 4.45mm  
 | | | | 180°SMT

DESCRIPTION: FEMALE HEADER 1.27\*1.27mm SMT TYPE, DUAL ROWS HEIGHT 4.4mm CAP+TAPE REEL