



RECOMMENDED P.C.B LAYOUT

SPECIFICATIONS

Material

Insulator : LCP, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze

Electrical

Current Rating : 0.5 Amp

Contact Resistance : 30 mΩ max.

Insulation Resistance : 1000 MΩ min.

Dielectric Withstanding Voltage : 250V AC for 1minute

Operating Temperature : -40°C to +105°C

HEIGHT	X	Y
22	2.1	2.25
35	3.4	3.55
44	4.3	4.45

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

照片框

ORDER INFORMATION

YAX-VxxZ-1XxxL-LF
SERIES
180°SMT
22:HIGH 2.25mm
35:HIGH 3.55mm
44:HIGH 4.45mm
LEADFREE
L TYPE FOOT POSITION
1X02:02WAY
1X50:50WAY
CLIP

DESCRIPTION: