



Material: *Insulator:Nylon 66 UL 94V-0

*Contact:Brass,Tin plating .

Dimensional Information:

Circuits	Dimensions			Pcs/Bag
	A	B	C	
2	2.00	4.75	5.98	1000
3	4.00	6.75	7.98	1000
4	6.00	8.75	9.98	1000
5	8.00	10.75	11.98	1000
6	10.00	12.75	13.98	1000
7	12.00	14.75	15.98	500
8	14.00	16.75	17.98	500
9	16.00	18.75	19.98	500
10	18.00	20.75	21.98	500
11	20.00	22.75	23.98	500
12	22.00	24.75	25.98	250
13	24.00	26.75	27.98	250
14	26.00	28.75	29.98	250
15	28.00	30.75	31.98	250
16	30.00	32.75	33.98	250

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4 PROJECTION

X, ±
.X ± 0.25
.XX ± 0.15
.XXX ± 0.08
ANG ±

照片框

ORDER INFORMATION

YH20-DK-xx-LF
SERIES | | LEADFREE
02~16WAY
KINK
DIP 180°

DESCRIPTION: