



Material:
Nylon 66 UL-94V-0

Circuits	Dimension mm				Qty/Bag
	A	B	C	D	
2	2.00	4.6	2.3	5.6	1000
3	4.00	6.6	2.3	7.6	1000
4	6.00	8.6	4.3	9.6	1000
5	8.00	10.6	4.3	11.6	1000
6	10.00	12.6	8.3	13.6	1000
7	12.00	14.6	10.3	15.6	1000
8	14.00	16.6	12.3	17.6	1000
9	16.00	18.6	12.3	19.6	1000
10	18.00	20.6	12.3	21.6	1000
11	20.00	22.6	16.2	23.6	1000
12	22.00	24.6	16.2	25.6	1000
13	24.00	26.6	16.2	27.6	1000
14	26.00	28.6	16.2	29.6	1000
15	28.00	30.6	16.2	31.6	1000
16	30.00	32.6	16.2	33.6	1000

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

P PROJECTION

X.±
.X±
.XX±
.XXX±
ANG±

照片框

ORDER INFORMATION

YH20-H-xx-LF
SERIES | LEADFREE
02~16WAY
HOUSING

DESCRIPTION: