



Specifications

- Voltage rating: 250V AC/ DC
- Current rating: 5A AC/ DC
- Withstanding Voltage: 1000V AC/minute.
- Insulation resistance: 1000MΩ Min.
- Temperature range: -25°C~+85°C
- Contact resistance: Initial Value/30mΩ Max

Wafer

- Poles : 04-50
- Material: Nylon 4T UL 94V-0
Pin: Brass/Tin-Plated
- Q'ty: 1,000 Pcs/Bag

PIN	"A"	"B"	PIN	"A"	"B"
04PIN	2.00	6.00	28PIN	26.00	30.00
06PIN	4.00	8.00	30PIN	28.00	32.00
08PIN	6.00	10.00	32PIN	30.00	34.00
10PIN	8.00	12.00	34PIN	32.00	36.00
12PIN	10.00	14.00	36PIN	34.00	38.00
14PIN	12.00	16.00	38PIN	36.00	40.00
16PIN	14.00	18.00	40PIN	38.00	42.00
18PIN	16.00	20.00	42PIN	40.00	44.00
20PIN	18.00	22.00	44PIN	42.00	46.00
22PIN	20.00	24.00	46PIN	44.00	48.00
24PIN	22.00	26.00	48PIN	46.00	50.00
26PIN	24.00	28.00	50PIN	48.00	52.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
.X ± 0.25
.XX ± 0.15
.XXX ±
ANG ±

照片框

ORDER INFORMATION

YHD20-R-xx-LF
SERIES | LEADFREE
04-50WAY
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: