



NOTE :

1. MAXIMUM ELECTRIC CURRENT : $\frac{\text{A.W.G.} \mid 16 \mid 14}{\text{AMP.} \mid 18 \mid 30}$
2. MAXIMUM ELECTRICAL RATING : $\triangle 105^{\circ}\text{C}$ 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.8 mm

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

YTS-V37-14-LF
SERIES | LEADFREE
14~16AWG
ID:3.7mm
PVC

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: