



A	COLOR	B
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
SHELL	BRAID	NC

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL2725 #28*1PR(WHITE, GREEN)+#28*2C(RED, BLACK) +AEB JACKET:BLACK OD:φ3.5 USB2.0	1PCS	E238846
2	CONN:	USB A TYPE MALE 4P WHITE 30U"	1PCS	
3	MOLDED:	PVC 45P BLACK	8.5G	
4	HOUSING:	ZHQ-H-04	1PCS	
5	TERMINAL:	ZHQ-T-24	4PCS	
6	SHRINK TUBE:	4φ*20mm BLACK F32	1PCS	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

UBZHQ-4A0428R1-F16N-LF

SERIES

LEADFREE
406.4mm
FEMALE TO FEMALE
ROUND CABLE
28 AWG
4 PIN ATYPE TO 04 WAY

DESCRIPTION: CABLE ASS'Y