

WW: WEEK
YY: YEAR

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY
1	WIRE:	UL1015 #22 RED	1PCS
2	WIRE:	UL1015 #22 BLACK	1PCS
3	WIRE:	UL1015 #22 WHITE	1PCS
4	WIRE:	UL1015 #22 GREEN	1PCS
5	H. S TUBE:	7φ*610mm RSFR-H BLACK	1PCS
6	LABEL:		1PCS

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

UL1015-040422-36N-LF

SERIES

LEADFREE

914.4mm

22AWG

04 TO 04 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y