



SPECIFICATIONS

Current rating : 3A AC,DC

Voltage rating : 250V AC,DC

Temperature range : -25°C to +85 °C

Contact resistance : 10mΩ Max.

Insulation resistance : 1000MΩ Min.

Withstanding voltage : 800V AC/minute

Material : Nylon 66, UL94V-0

Poles	Dimension mm (in.)	
	A	B
2	2.50 (0.098)	5.70(0.224)
3	5.00 (0.197)	8.20(0.323)
4	7.50 (0.295)	10.70(0.421)
5	10.00 (0.394)	13.20 (0.520)
6	12.50 (0.492)	15.70(0.618)
7	15.00 (0.591)	18.20(0.717)
8	17.50 (0.689)	20.70(0.815)
9	20.00 (0.787)	23.20(0.913)
10	22.50 (0.886)	25.70(1.012)
11	25.00 (0.984)	28.20(1.110)
12	27.50 (1.802)	30.70(1.209)
13	30.00 (1.181)	33.20(1.307)
14	32.50 (1.280)	35.70(1.406)
15	35.00 (1.378)	38.20(1.504)
16	37.50 (1.476)	40.70(1.602)
20	47.50 (1.870)	50.70(1.996)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30
.X ± 0.30
.XX ± 0.20
.XXX ± 0.20
ANG ± 0.20

P PROJECTION



ORDER INFORMATION

XH-H-xx-LF
SERIES | LEADFREE
02-20WAY
HOUSING

DESCRIPTION: