


RECOMMENDED P.C.B LAYOUT  
TOLERANCES: ±0.05mm

PARTS DIMENSION TABLE



parts no.	DIM. a	DIM. b	inner thread
B	4.8	11.8	4#40
C	4.8	11.8	4#40
D	5.8	12.0	4#40
E	5.8	12.0	4#40

**MATERIAL-**

Insulator: Nylon 6T (Black), UL94V-0.  
Contact: Phosphor Bronze or Brass (Standard is Brass)  
Contact Plating: GOLD Plating Over NICKEL In Contact Area.  
Tin Plating Over Nickel In Dip Area.  
NICKEL Plating In A'SS AREA.

Shell: Steel, Nickel Plated.

**SPECIFICATION-**

Current Rating: 5amps.  
Insulator Resistance: 1000M $\Omega$  Min. at 500V DC.  
Contact Resistance: 20mill $\Omega$  Max.  
Withstanding Voltage: 1000V AC/minute.  
Reflow Processing Temperature & Time: 240°C For 6 Seconds.  
Peak Reflow Processing Temperature & Time: 230°C For 60 Seconds.  
Operating Temperature: -55°C~ +125°C.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X,  $\pm$   
.X  $\pm$   
.XX  $\pm$   
.XXX  $\pm$   
ANG  $\pm$

PPOJECTION



ORDER INFORMATION

DR13-SNJ-25-LF

SERIES | | | LEADFREE  
| | | 25 WAY  
| | | JACKSCREW  
| | | NUT  
| | | FEMALE

DESCRIPTION: