

MATERIAL & FINISH

- * Contact: Beryllium Copper (BeCu)
- * Sleeve: Brass
- Plating: G=Gold Plated
T=Tin Plated
- * Insulator: IC Socket=PBT
- * Insertion Standard Force: Average 300 GR
- * Extraction Standard Test: Average 60 GR
- * Resist to Soldering Heat: Max. 120~130°C, 5 Sec.
- * Current Rating: 1A
- * Operating Humidity Range: Annual mean 75%
- * Contact Resistance : 10 Milliohm
- * Insulator Resistance : 5000 Mege Ohm at 500 VDC
- * Dielectric Strength : 1000 VRMS Min
- * Rated Voltage : 100 VRMS / 150VDC
- * Temperature: - 55°C TO + 125°C

TYPE	DIM 2	DIM A	DIM B	DIM C
06	7.62	7.62	10.16	
08	10.16	7.62	10.16	
10	12.70	7.62	10.16	
14	17.78	7.62	10.16	
16	20.32	7.62	10.16	
18	22.86	7.62	10.16	
20	25.40	7.62	10.16	
22	27.94	7.62	10.16	
24	30.48	7.62	10.16	
28	35.56	7.62	10.16	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

SIW-D03-xx-LF
SERIES | LEADFREE
06-28WAY
SPACING 7.62mm
DIP 180°

DESCRIPTION: SCREW MACHINE PIN IC SOCKET WIRE WRAP