



MATERIAL:

INSULATOR : PBT, UL 94V-0.△
 CONTACT : COPPER ALLOY.
 CONTACT FINISH : GOLD OVER NICKEL.
 SHELL : STEEL.
 BOARDLOCK : BRASS, TIN PLATED.
 RIVETED INSERT : BRASS, NICKEL PLATED.

SPECIFICATION:

CURRENT RATING : 5 AMP
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC FOR 1 MINUTE.
 INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.
 CONTACT RESISTANCE : 15mΩ MAX.
 OPERATING TEMPERATURE : -55°C ~ +105°C.

POSITION	A ± 0.20	B ± 0.20	C ± 0.38	D
09 PIN	16.90	25.00	30.80	11.08
15 PIN	25.25	33.30	39.20	19.39
25 PIN	38.95	47.05	53.05	33.24
37 PIN	55.40	63.50	69.40	49.86

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 ANG ±

PJECTION



ORDER INFORMATION

DRL-PGN-xx-LF
 SERIES | | LEADFREE
 | | 09~37WAY
 | NUT
 | FULL GOLD
 MALE

DESCRIPTION: D-SUB CONN RIGHT ANGLE , MALE FOOTPRINT : 14.84mm

煜倫股份有限公司

www.morethanall.com