



P.C.B LAYOUT

Technical Data

Material:

Pin(outer sleeve): Brass,machined CuZn38Pb2

Clip(cotact 4 fin Phosphor Bronze heat treated

Plating(outer sleeve):

Tin plated:2um/80u"Ni, 5um/200u"Sn

Gold Plsted:2um/80u"Ni,Full gold

Plating(cotact): 2um/80u"Ni, gold or Tin plated

Insulator(black): Glass filled thermoplastic polyester

UL94 V-0

Electrical:

Current rating: 3Amps/contact max.

Contact resistance: $\leq 4m\Omega$ /contact

Insulation resistance: $\geq 1000M\Omega$ at V=100V

Operaing voltage: 60VAC/DC

Mechanical:

Average insertion force with steel pin of

$\phi 0.43mm/0.017"$: <250g

Average withdrawal force with steel pin of

$\phi 0.43mm/0.017"$: >50g min.

Mechanical life cycle:min.200

Operaing temperatures: Gold Plsted:-55°FXC to+105°FXC

Tin plated:-40°FXC to+105°FXC

Soldering temperature: +260°FXC,10s max.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±

.X ±

.XX ±

.XXX ±

ANG ±



ORDER INFORMATION

SS-DEE-1X02-LF
SERIES | LEADFREE
02 WAY
EMPTY EVEN PIN
DIP 180°

DESCRIPTION: 2.54mmPitch IC Sockets DIP Pin Length 7.43mm