



**MATERIALS AND FINISH**

SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED  
 BACK SHELL TIN FINISHED  
 DIMPLES ON PLUG ONLY  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,  
 UL 94V-0 RATED, BLACK COLOR  
 SIGNAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

**ELECTRICAL CHARACTERISTICS**

CONTACT CURRENT RATING : 5.0 AMPS  
 CONTACT RESISTANCE : 10 mΩ MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.  
 INSULATION RESISTANCE : 5GΩ MIN.  
 TEMPERATURE RATING : -55°C ~ +125°C

**RoHS Compliant**

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X, ±

.XX, ±

.XXX, ±

ANG, ±

PPOJECTION



**ORDER INFORMATION**

DWS-S-07W2-LF  
 SERIES | LEADFREE  
 07W2  
 FEMALE

DESCRIPTION: