

POSITION	A ± 0.20	B ± 0.20	C ± 0.38	D
09 PIN	16.30	25.00	30.80	11.08
15 PIN	24.60	33.30	39.20	19.39
25 PIN	38.35	47.05	53.05	33.24
37 PIN	54.80	63.50	69.40	49.86

**MATERIAL:**

INSULATOR : PBT, UL 94V-0.  $\Delta$   
 CONTACT : COPPER ALLOY.  
 CONTACT FINISH : GOLD OVER NICKEL.  
 SHELL : STEEL.  
 BOARDLOCK : BRASS, TIN PLATED.  
 RIVETED INSERT : BRASS, NICKEL PLATED.

**SPECIFICATION:**

CURRENT RATING : 5 AMP  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC FOR 1 MINUTE.  
 INSULATION RESISTANCE : 1000M $\Omega$  MIN. AT 500V DC.  
 CONTACT RESISTANCE : 15m $\Omega$  MAX.  
 OPERATING TEMPERATURE : -55°C ~ +105°C.

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

PPOJECTION



**ORDER INFORMATION**

DRF-SGN-xx-LF  
 SERIES | | | LEADFREE  
 | | | 09~37WAY  
 | | | NUT  
 | | | FULL GOLD  
 | | | FEMALE

**煜倫股份有限公司**

www.morethanall.com

DESCRIPTION: