

- MATERIAL & FINISH**
- * Contact: Beryllium Copper (BeCu)
 - * Sleeve: Brass
 - Plating: G=Gold Plated
T=Tin Plated
 - * Insulator: IC Socket=PBT
 - * Insertion Standard Force: Average 300 GR
 - * Extraction Standard Test: Average 60 GR
 - * Resist to Soldering Heat: Max. 120~130°C, 5 Sec.
 - * Current Rating: 1A
 - * Operating Humidity Range: Annual mean 75%
 - * Contact Resistance : 10 Milliohm
 - * Insulator Resistance : 5000 Mege Ohm at 500 VDC
 - * Dielectric Strength : 1000 VRMS Min
 - * Rated Voltage : 100 VRMS / 150VDC
 - * Temperature: - 55°C TO + 125°C

TYPE	DIM 1	DIM A	DIM B	DIM C
20		25.40	15.24	17.78
24		30.48	15.24	17.78
28		35.56	15.24	17.78
32		40.64	15.24	17.78
36		45.66	15.24	17.78
40		50.80	15.24	17.78
42		53.34	15.24	17.78
48		60.96	15.24	17.78

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1


DATE

SIZE A4

TOLERANCES ARE

- X. ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

PJECTION



ORDER INFORMATION

SIW-D06-xx-LF
SERIES | LEADFREE
20~48WAY
SPACING 15.24mm
DIP 180°

DESCRIPTION: SCREW MACHINE PIN IC SOCKET WIRE WRAP