



**SPECIFICATION**

**MATERIAL**

Insulator: Polyester resin and glass fiber reinforced (UL94V-0)

Contacts: Brass

**CONTACT PLATING**

Contact area: Gold flash

Solder tails: 100u" Tin over 40u" Nickel

**ELECTRICAL**

Operation voltage: 250 VAC max.

Current rating: 3 Amps max.

Contact resistance: 15 mohms max.

Insulation resistance: 3000 Mohms min @ 500 VDC

Dielectric withstanding voltage: 1000 VAC / minute

Operating temperature: -55°C TO +105°C

POSITION	A	B	C	D
DFM-PN-09	16.92	25.00	30.8	22.4
DFM-PN-15	25.25	33.30	39.2	30.8
DFM-PN-25	38.96	47.10	53.1	44.5
DFM-PN-37	55.42	63.50	69.4	61.4

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ±

PPOJECTION



**ORDER INFORMATION**

DFM-PN-xx-LF  
SERIES | T LEADFREE  
| 09-37WAY  
| NUT  
| MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: D-SUB IDC FOR FLAT RIBBON CABLE