

P. C. B . LAYOUT

A: 16.34 mm

B: 7.70 mm

C: 6.10 mm

MATERIAL

HOUSING :PBT, UL-94V0
 CONTACT :COPPER ALLOYS
 PLATED :GOLD FLASH
 COLOR :BLACK

SPECIFICATION

CURRENT : 3A
 OPERATING TEMPERAURE : -55° C TO +105° C
 CONTACT RESISTANCE : 20 MILLIOHMS MAX
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN
 WITHSTAND VOLTAGE : 1000 V AC/minute

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PPOJECTION

X. ±
 .X ± 0.38
 .XX ± 0.25
 .XXX ±
 ANG ± 5°



ORDER INFORMATION

H-D163077061-1X04E2-LF
 SERIES | | | | LEADFREE
 | | | | EMPTY#2
 DIP 180° | | | |
 | | | | CONTACT 7.7mm
 | | | | TOTAL LENGTH 16.34mm

DESCRIPTION: 2.54PH 180° H:2.54 1*4(N2) PIN