



类型	小直键开关	品名	PSW2525-R-06
1. 功能规格			
1.1 额定电压	DC50V	1.6 自由位置 (FP)	
1.2 额定电流	0.3A	1.7 动作位置 (OP)	
1.3 接触电阻 (CR)	≤50mΩ (初始值)	1.8 行程 (PT)	2.5±0.2mm LOCK (S)
1.4 操作力 (OF)	250±100gf	1.9 全行程 (TT)	3.5±0.2mm FULL (S)
1.5 回弹力 (RF)			
2. 可靠度参数			
2.1 机械寿命	10,000 CYCLES	2.5 焊接工艺	手工焊
2.2 电气寿命	10,000 CYCLES	2.6 操作温度	-10℃ ~ +60℃
2.3 绝缘电阻 (IR)	≥100MΩ DC500V	2.7 储存湿度	<85%RH
2.4 耐压强度 (WV)	AC250V 1 minute	2.8	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION



ORDER INFORMATION

PSW2525-R-06-LF

SERIES

LEADFREE

06 WAY

DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: