



PCB LAYOUT

NOTE:

- SOLDER TAIL TO BE WITHIN 0.05 UPWARD AND 0.2 DOWNWARD FROM Z-DATUM PLACE, AND COPLANALITY OF SOLDER TAILS TO BE WITHIN 0.10  
MEASUREMENT POINT IS SOLDER TAILS TIP.
- INSPECTION SYMBOL:  
● : MANUFACTURER INSPECTION  
◆ : Q.C INSPECTION

CIRCUIT



WITHOUT CARD

CARD INSERTED

Pin #	Name
C1	VCC
C2	MCLR
C3	RB6/Osc1
C5	VSS
C6	VPP
C7	RB7

SOLDER AREA

NO PATTERN AREA

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION



ORDER INFORMATION

SCP-W14PAA25-06-LF  
SERIES  
90°SMT  
LEADFREE  
06WAY  
EAR/POST 2.5mm  
SWITCH CLOSED  
POST  
POST TO POST 14.0mm

DESCRIPTION: