

④	45P PVC COLOR:BLACK	CMB05059	CMB06238	0.0045	Kg
③	PE	CMB05058	CMB06112	0.0017	Kg
②	UL21149 7P SERIAL ATA CABLE 26AWG COLOR:RED(16043) OD:2.2*7.8±0.20mm			490	mm
①	S-ATA-7P BLACK MOLDING 3u"			2	pcs
NO.	DESCRIPTION			Q'TY	UNIT

ELECTRONIC TEST:

1. ALL CABLE 100% TEST, OPEN, SHORT, MISSWIRE
2. RESISTANCE: 2 ohm max
3. I. RESISTANCE: 10M ohm min
4. HI-POT: 500V DC/10ms
5. DIMENSIONS MARK "▼" SHOULD BE CHECKED;

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

SATA X2-7R7S26-Fxxx-LF

SERIES

LEADFREE
2N5:2.5"
50C:50CM
FEMALE TO FEMALE
26 AWG
7 PIN 90° TO 7 PIN 180°

DESCRIPTION: