

A	COLOR	B	C
1	YELLOW	1	
2	BLACK	2	
	BLACK	3	
3	BLACK		2
	BLACK		3
4	YELLOW		1

JUMP WIRE (between B2/B3 and C2/C3)
 JUMP WIRE (between C2/C3 and C1)

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #20 YELLOW	2PCS	E108485
2	WIRE:	UL1007 #20 BLACK	2PCS	E108485
3	WIRE:	UL1007 #20 BLACK	2PCS	E108485
4	HOUSING:	MIF-SH-1X04	1PCS	E115256
5	TERMINAL:	MIF-FT-20	4PCS	
6	HOUSING:	DP-P-04	2PCS	E149293
7	TERMINAL:	DP-M-18	6PCS	
8				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

DPMIFX21-040420-E12N-LF

SERIES

LEADFREE
304.8mm
MALE TO FEMALE
20 AWG
04 TO 04 WAY

DESCRIPTION: CABLE ASS'Y