



MATERIALS:

1. HOUSING: THERMOPLASTIC, UL 94V-0 RATED.
2. COVER: THERMOPLASTIC, UL 94V-0 RATED.
3. CONTACTS: COPPER ALLOY, SELECTIVE GOLD PLATED
4. SHELL: SPCC, NICKEL PLATED.
5. HARPOON: COPPER ALLOY, TIN OVER NICKEL

SPECIFICATION:

1. RATED CURRENT: 0.30A/CONTACT
2. INSULATION RESISTANCE: 500MOHM MIN.
3. DIELECTRIC WITHSTANDING VOLTAGE: 250V AC FOR 1 MINUTE.
4. OPERATING TEMPERATURE: -25°C TO +85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
X, ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

VHCB1-SRNZ2-068-LF

SERIES | | | | LEADFREE
| | | | 68 WAY
| | | |
| | | | CLIP
| | | | NUT
| | | | DIP 90°
| | | | FEMALE

DESCRIPTION: 68 POSITION CHAMP STACKED PITCH 0.80, RIGHT ANGLE TYPE

煜倫股份有限公司

www.morethanall.com