



NOTES:

1. MATERIAL:
 - 1.1 HOUSING: PBT+30%GF UL94V-0 BLUE
 - 1.2 CONTACT: PHOSPHOR BRONZE OR BRASS
 - 1.3 SHELL: SPCC
2. FINISH:
 - 2.1 CONTACT:
 - AU PLATED ON CONTACT AREA
 - TIN PLATED ON SOLDER AREA
 - NICKEL UNDERPLATING OVER ALL
 - 2.2 SHELL :
 - NICKEL PLATED
3. SPECIFICATIONS:
 - 3.1 CONTACT CURRENT RATING:
 - 1.8 AMPERES FOR PIN1&PIN4
 - 0.25 AMPERES OTHER CONTACTS
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE:AC 100V(RMS)
 - 3.3 INSULATION RESISTANCE:100MEG OHMS MIN.
 - 3.4 CONTACT RESISTANCE:30mΩ MAX. FOR PIN1&PIN4
50mΩ MAX FOR OTHER CONTACTS.
 - 3.5 MECHANICAL CHARACTERISTICS:
 - MATING FORCE:35 NEWTOMS. MAX.
 - UNMATING FORCE:10 NEWTOMS. MIN.
 - 8N NEWTOMS. AFTER DURABILITY.
 - 3.6 OPERATING TEMPERATURE:-55° TO +85°.

Pin Number	Signal Name	Pin Number	Signal Name
1	VBUS	5	SSRX-
2	D-	6	SSRX+
3	D+	7	GND
4	GND	8	SSTX
Shell	Shield	9	SSTX+

ITEM	PART NAME	Material	Q'TY	REMARK
1	Contact	COPPER ALLOY	5	T=0.25 Plating Gld/Tin
	Contact	COPPER ALLOY	4	T=0.25 Plating Gld/Tin
	Housing	PBT	1	Black &Blue UL94V-0
	COVER	PBT	1	Black &Blue UL94V-0
2	FRONT Shell	SPCC	1	T=0.3 Plating NI
3	BLACK Shell	SPCC	1	T=0.3 Plating NI

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

X. ± 0.30
.X ± 0.25
.XX ± 0.20
.XXX ± 0.15
ANG ± 5°

P PROJECTION



ORDER INFORMATION

USB-PSBL-9B-LF
SERIES | | | LEADFREE
9 PIN B TYPE
BLUE
SOLDER
MALE

DESCRIPTION: USB3.0 B/M SOLDER OD:φ6.0