

NOTES:

PLATING:

TERMINAL: 50~80U" NI UNDER PLATE ALL  
OVER. MIN 3U"GOLD PLATED IN CONTACT AREA

ELECTRICAL SPECIFICATION:

CURRENT RATING: 0.8A  
VOLTAGE RATING: 250VAC  
WITHSTANDING VOLTAGE: MIN 300VAC  
INSULATION RESISTANCE: MIN 100MΩ  
CONTACT RESISTANCE: MAX 80mΩ

ENVIRONMENTAL

OPERATING TEMPERATURE: -15°C TO +85°C  
STORAGE TEMPERATURE: -30°C TO +85°C

		TOLERANCE				
		X.	X.X	X.XX	X.XXX	X.°
	A	± 0.20	± 0.10	± 0.05	± 0.03	± 1°
	B	± 0.50	± 0.20	± 0.10	± 0.05	± 2°
✓	C	± 0.80	± 0.40	± 0.20	± 0.10	± 3°

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±


DATE

.XXX ±

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

IPD-JW-30-LF  
SERIES | LEADFREE  
30 WAY  
90°SMT  
JACK

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: I POD 30P SOCKET