

SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 500MΩ Min
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	2.50	5.00	09P	20.00	22.50
03P	5.00	7.50	10P	22.50	25.00
04P	7.50	10.00	11P	25.00	27.50
05P	10.00	12.50	12P	27.50	30.00
06P	12.50	15.00	13P	30.00	32.50
07P	15.00	17.50	14P	32.50	35.00
08P	17.50	20.00	15P	35.00	37.50

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES


DRAWING BY CY
 CHECKED BY GENIUS
 UNIT/mm SCALE 1:1
 DATE

X. ±
 .X ± 0.20
 .XX ± 0.10
 .XXX ±
 ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4 PROJECTION



ORDER INFORMATION

EI-D-xx-LF
 SERIES | LEADFREE
 02-15WAY
 DIP 180°

DESCRIPTION: 2.50mm PITCH 180° WAFER