



MATERIALS:
 INSULATOR:P.B.T.30%GLASS FIBER,UL94V-0
 SR:INSULATOR: P.C. UL94V-2
 CONTACT MATERIAL:BRASS OR PHOSPHOR BRONZE,GOLD FLASH OVER NICKEL
 NSR: P.C. FIBER,UL94V-0

ELECTRICAL:
 CURRENT RATING:1AMP DC
 INSULATION RESISTANCE:3000MΩ MIN.
 CONTACT RESISTANCE:30mΩ MAX.
 DIELECTRIC WITHSTANDING:500V AC
 OPERATING TEMPERATURE:-40°C~+105°C
 TERMINATED WITH 1.27mm PITCH FLAT RIBBON CABLE.

@: Table-1

DIMENSION				
CONTACT	A	B	D	E
10P	17.26	10.16	3.60	13.70
14P	22.34	15.24	3.60	18.78
16P	24.88	17.78	3.60	21.30
20P	29.96	22.86	3.60	26.38
24P	35.04	27.94	3.60	31.46
26P	37.58	30.48	3.60	34.00
30P	42.66	35.56	3.60	39.08
34P	47.74	40.64	3.60	44.48
40P	55.36	48.26	3.60	52.10

RoHS Compliant

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司

www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1:1
 DATE

TOLERANCES ARE
 X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

SIZE A4 PPROJECTION



ORDER INFORMATION

F-C3L-xx-LF
 SERIES | LEADFREE
 | 06-50WAY
 | SR / LOCK
 | THREE TYPE

DESCRIPTION: