



MATERIAL:

- A. INSULATOR:PC(94V-2)&GLASS-FIBER
- B. CONTACT:BRONZE
- C. CONTACT PLATED:TIN PLATED

SPECIFICATION:

- A. CURRENT RATE:3A/250V AC
- CONTACT RESISTANCE:
 - A. (BRONZE)11.5m AT 2VΩ DC 100mA
 - B. (PHOSPHOR BRONZE)10.9m AT 2VΩ DC 100mA
 - C. INSULATOR RESISTANCE:1.5G ATW 500V DC 1Min
 - D. Dielectric withstanding:1000Vac 1Min

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4 PPROJECTION



ORDER INFORMATION

SC-SRLH-21-LF
SERIES | LEADFREE
21 WAY
HOLE
FEMALE | LOCK
DIP 90°

DESCRIPTION: Double Scart Socket with Center Screw Mounting Holes(OD=2.4)