


SCREW A TYPE FOR LOCK INSULATOR (4 PCS)



SCREW B TYPE FOR LOCK SR (2 PCS)

MECHANICAL

INSULATOR MATERIAL:

PBT & Glass-fibre reinforced
UL 94V-0, 1 Pcs

HOOD MATERIAL:

Aluminum, 1 Pcs

THUMSCREW MATERIAL:

Copper Alloy, 2 Pcs

SCREW FOR LOCK INSULATOR MATERIAL:

Steel, 4 Pcs

SCREW FOR LOCK SR MATERIAL:

Steel, 2 Pcs

WIRE SIZE:

AWG 24 or 26 or 28

ELECTRICAL

CURRENT RATING:

7 Amp

WITHSTANDING VOLTAGE:

AC 1200V Min. (for one minute)

INSULATION RESISTANCE:

1000M Ω Min.(at 500V DC)

CONTACT RESISTANCE:

10m Ω Max. mated

WORKING TEMPERATURE:

-55° C to +105° C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.30

CHECKED BY GENIUS

.X ± 0.25

UNIT / mm

SCALE 1 : 1


.XXX \pm

DATE

ANG $\pm 3^\circ$

SIZE A4

PPOJECTION



ORDER INFORMATION

V35-SHW-34-LF
SERIES | LEADFREE
34WAY
WHITE COVER
HOUSING
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: V. 35 CONNECTOR FEMALE WITH PLASTIC SR WITHOUT PIN