



NO.	Description	Material	Q'TY	Finish
5.	Housing	PE	1	Black Color
4.	Terminal	0.6T Bronze	1	Nickel Plated
3.	Ground Terminal	0.4T Bronze	1	Nickel Plated
2.	Outer Sleeve	Brass	1	Nickel Plated
1.	Insulator Ring	POM	1	Black Color

**SPECIFICATIONS:**  
 Contact Resistance : 30mΩ max  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 X, ±  
 .XX ±  
 .XXX ±  
 ANG ±

PJECTION



**ORDER INFORMATION**

**DCP-ALK-5525-LF**  
 SERIES | LEADFREE  
 ID: 2.5Ø  
 OD: 5.5Ø  
 LOCK  
 ASSEMBLY

DESCRIPTION:

**煜倫股份有限公司**

[www.morethanall.com](http://www.morethanall.com)