


RECOMMENDED PCB LAYOUT ±0.10mm



VIEW A
SCALE 4 : 1

MATERIAL:

INSULATOR : PBT, UL 94V-0.

CONTACT : COPPER ALLOY.

CONTACT FINISH : GOLD ON MATING END, TIN ON
TERMINATION END, WITH ENTIRE
CONTACT NICKEL UNDERPLATED.

SHELL : STEEL.

SPECIFICATION:

CURRENT RATING : 5 AMP

DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC FOR 1 MINUTE.

INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.

OPERATING TEMPERATURE : -55°C ~ +105°C.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

HDR50-SSN-15S9-LF

SERIES	NUT	LEADFREE
	SEMI GOLD	SHORT #9
	FEMALE	15WAY

DESCRIPTION: HIGH DENSITY D-SUB CONN. RIGHT ANGLE
15PIN FEMALE FOOTPRINT : 5.08mm

煜倫股份有限公司

www.morethanall.com