



Material:  
 Insulator: PBT+30% Glass Fiber (UL94V-0).  
 Contact: Copper Alloy.  
 Contact Plated: Gold or Tin over Nickel Plated.  
 Shell: Steel with Nickel or Tin or Zinc Plated.

Specification:  
 Current Rating: 5 Amps.  
 Withstanding Voltage: AC 500V for 1 Minute.  
 Insulation Resistance: 1000MΩ Min. at DC 500V.  
 Contact Resistance: 15mΩ Max..  
 Operating Temperature: -40°C ~ +105°C.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±

DATE

.XXX±

ANG±

SIZE A4

P PROJECTION



ORDER INFORMATION

**HDR-SGNJ-15-LF**  
 SERIES | | | | | LEADFREE  
 | | | | | 15WAY  
 | | | | | JACKSCREW  
 | | | | | NUT  
 | | | | | FULL GOLD  
 | | | | | FEMALE

DESCRIPTION: 15P Hi-Density Female D-Sub Right Angle Connector Footprint 8.89mm Short Pin 9th Clinch Nut/Screw Lock Type

煜倫股份有限公司

www.morethanall.com