



PCB LAYOUT (BOTTOM VIEW) TOLERANCE: ±0.05

NOTES:

1. MATERIALS:

INSULATOR: GLASS FIBER REINFORCED THERMOPLASTIC LCP UL94V-0.
 CONTACT: PHOSPHOR BRONZE, GOLD FLASH ON CONTACT, TIN PLATED ON TAIL 100µ", OVER NICKEL PLATED 50µ".
 SHELL: SPCC, NICKEL PLATED.
 BOARD LOCK: BRASS, TIN PLATED.
 RIVET: BRASS, NICKEL PLATED.

2. ELECTRICAL:

INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM
 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC
 VOLTAGE RATING: 40 VOLTS AC(RMS) MAXIMUM
 CURRENT RATING: 3.0 AMPS PER CIRCUIT
 CONTACT RESISTANCE: 20 MILLIOHMS MAXIMUM

3. MECHANICAL PERFORMANCE:

MATING FORCES: 4.5kgf MAXIMUM
 UNMATING FORCES: 1kgf MINIMUM, 4kgf MAXIMUM
 DURABILITY: 100 CYCLES MINIMUM

4. ENVIRONMENTAL:

TEMPERATURE RANGE: -20°C TO +85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

DVI-SRJN-24+5-LF
 SERIES | | | LEADFREE
 | | | 24+5 PIN
 | | | JACKSCRW
 | | | NUT
 | | | DIP 90°
 | | | FEMALE

DESCRIPTION: DVI 24+5Pin 90度母座半金貝吉色無後鐵殼(BC)鎖螺絲