

RECOMMENDED P.C.B. LAYOUT

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

Contact Current Rating:3 Amperes.
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.
 Insulation Resistance:5000 Medohms Minimum.at DC 500V.
 Contact Resistance:25 Milliohms Maximum.
 Operating Temperature:-55°C to+105°C.

MECHANICAL CHARACTERISTICS:

Contact Insertion Force:341 g.Maximum.
 Contact Separation Force:21 g.Maximum.

MATERIALS:

Contacts:Brass.
 Insulator: PBT or HIGH TEMP THERMAL PLASTIC 94V-0 Rated.
 Shell:Cold Roller Steel.

FINISHES:

Contact:Gold Flash.
 Shell:Nickel Plated.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ±
 ANG ±



ORDER INFORMATION

HDR15-SNRVZ1-15-LF
 SERIES | NUT | CLIP REVERSED | LEADFREE 15 WAY | FEMALE

DESCRIPTION: D-SUB 15 FEMALE HIGH DENSITY CONN.SLIM DIP TYPE RIGH ANGLE 1.60mm FOOTPRINT,1.50mm ROW DISTANCE