

RECOMMENDED P. C. B. LAYOUT

## SPECIFICATIONS

### ELECTRICAL CHARACTERISTICS:

Contact Current Rating:3 Amperes.  
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.  
 Insulation Resistance:5000 Medohms Minimum.at DC 500V.  
 Contact Resistaance:25 Milliohms Maximum.  
 Operating Temperature:-55°C to+105°C.

### MECHANICAL CHARACTERISTICS:

Contact Insertion Force:341 g.Maximum.  
 Contact Seperation Force:21 g.Minimum.

### MATERIALS:

Contacts:Brass.  
 Insulator: PBT UL 94V-0 Rated.  
 Shell: Cold Roller Steel.

### FINISHES:

Contact:Gold Flash.  
 Shell:Nickel Plated.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±


DATE

.XXX±

ANG±

SIZE A4

P PROJECTION



### ORDER INFORMATION

HDR30-SSNJBL-15-LF

SERIES | | | | LEADFREE  
 | | | | 15WAY  
 FEMALE | | BLUE  
 | | JACKSCRW  
 NUT  
 SEMI GOLD

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: **MINI BODY D-SUB CONNECTOR 0.121"(3.08mm) FOOTPRINT,RIGHT ANGLE**