



NOTES:

- 1.0 CONNECTOR ELECTRICAL CHARACTERISTICS:
- 1.1 CONTACT CURRENT RATING: 1.0 AMPERE
- 1.2 DIELECTRIC WITHSTANDING VOLTAGE: AC 500 V r.m.s.
- 1.3 INSULATION RESISTANCE: 500 MEGOHMS Min.
- 1.4 CONTACT RESISTANCE: 35 MILLIOHMS Max.
- △ 1.5 OPERATING TEMPERATURE: -55°C TO +85°C

TABLE C:

5	HOOK	2	STAINLESS
4	FRONT SHELL	1	STEEL/ NI PLATED OVER COPPER
3	RIVET	2	COPPER/ TIN PLATED
2	HOUSING	1	THERMOPLASTIC, WITH GLASS FILLED/ UL 94V-0 RATED, BLACK
1	CONTACT	N	COPPER ALLOY/ SELECTIVE GOLD PLATING
ITEM	NAME	Q'TY	MATERIAL / FINISH

TABLE A:

PART NO.	NO. OF POSN.	DIM. A	DIM. B	DIM. C	DIM. D	DIM. E	DIM. F ±0.25
HPC-SDL-014	14	29.57	23.64	12.62	7.62	20.04	16.94
HPC-SDL-020	20	33.38	27.45	16.43	11.43	23.85	20.75
HPC-SDL-026	26	37.19 △	31.26	20.24	15.24	27.66	24.64
HPC-SDL-036	36	43.54	37.61	26.59	21.59	34.01	30.91
HPC-SDL-050	50	52.43	46.50	35.48	30.48	42.90	39.88
HPC-SDL-068	68	63.86	57.93	46.91	41.91	54.33	51.31
HPC-SDL-080	80	71.48	65.55	54.53	49.53	61.95	58.93

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

HPC-SDL-xxx-LF
SERIES | | | LEADFREE
014~080WAY
LOCK
DIP 180°
FEMALE

DESCRIPTION: HALF PITCH CONNECTOR, FEMALE RIBBON TYPE VERTICAL T/H