



ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55°C TO +105°C.

MECHANICAL CHARACTERISTICS:

CONTACT INSERTION FORCE: 4.0 KG MAXIMUM.
 CONTACT SEPARATION FORCE: 0.5 KG MINIMUM.

MATERIALS:

CONTACT: PHOSPHOR BRONZE.
 INSULATOR: NYLON 6T
 SHELL: STAINLESS.
 HOOD: NYLON66+15GF

FINISHES:

CONTACTS: GOLD FLASHED 10U", 15U", 20U", 30U".

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION



ORDER INFORMATION

MSB-PA-4H-LF
 SERIES | T LEADFREE
 | 4 PIN H TYPE
 | ASSEMBLY
 MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MINI U.S.B. 4PIN(M) (HRS) 裝配式 (單面防呆)