

Recommend P.C.B LAYOUT

備註 / NOTE:

1. 安規
 - 1-1. 規格 / RATING: 5V / 1A
 - 1-2. 絕緣阻抗 / Insulation Resistance: 100M ohm Min at DC 500V
 - 1-3. 絕緣耐壓 / Dielectric Withstanding Voltage: AC100V for 1 Minute
 - 1-4. 接觸阻抗 / Contact Resistance: 30m ohm or less
2. 材質 / MATERIAL:
 - 2-1. 膠芯 / Housing: LCP
 - 2-2. 針 / Pin: 磷銅 / PHOSPHOR BRONZE
 - 2-3. 銅殼 / Shell: 黃銅 / BRASS
3. 電鍍 / electroplate
 - 3-1. 針 / Pin: 半金10u"鍍金 / GOLD10u"鍍
 - 3-2. 銅殼 / Shell: 霧銅 / TIN

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±
X, ±
.XX ± 0.20
.XXX ± 0.10
ANG ±

P PROJECTION



ORDER INFORMATION

MSB-SWFEMC-5AB-LF
SERIES | | | | | LEADFREE
FEMALE | | | | | 5 PIN AB TYPE
90° SMT | | | | | MYLAR
EAR | | | | | METAL LEG
OFFSET

DESCRIPTION: MINI USB 5PIN(F) 沉板式 DIP