

NOTES:

1:Material:

- 1.1 Housing: Thermoplastic UL94V-0 color:black.
- 1.2 Contact: Phosphor bronze T=0.30mm.
- 1.3 Shell: Copper alloy T=0.4mm.
- 1.4 Spacer: Thermoplastic UL94V-0 color:black.

2:Specification:

- 2.1 Current rating: 0.5 A Max.
- 2.2 Voltage rating: 4D V AC(rms) Max.
- 2.3 Contact resistance: 50 mW Max.
- 2.4 Dielectric withstanding
voltage: 100 V(ac) for 1 min.
- 2.5 Insulation resistance: 1000 MW Min.
- 2.6 Operation temperature range: -25°C~85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

HDMI-PM-19-LF
SERIES | LEADFREE
19 WAY
MOLDING
MALE

DESCRIPTION: HDMI-19P 夾板

www.morethanall.com